

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

METHOD AND COATING SYSTEM FOR REDUCING CARBONACEOUS DEPOSITS ON SURFACES EXPOSED TO HYDROCARBON FUELS AT ELEVATED TEMPERATURES

Background of Invention

Field of the Invention

[0001] The present invention relates to coatings that inhibit the formation and adhesion of deposits on surfaces that contact hydrocarbon fluids. More particularly, this invention relates to a method and coating system for preventing or reducing the deposition of carbonaceous deposits on surfaces that contact a hydrocarbon fluid at high temperatures.

Description of the Related Art

[0002] Thermal instability, or in the case of fuels, fuel instability, generally refers to the formation of undesired deposits that occurs when hydrocarbon fluids, such as fuels and lubricating oils, are at high temperatures, generally above about 140 ° C. In the case of fuels, it is generally accepted that there are two distinct mechanisms occurring within two overlapping temperature ranges. In the first mechanism, referred to as the coking process, a generally consistent increase in the rate of formation of coke deposits occurs above temperatures of about 650 ° F (about 345 ° C). Coke formation is the result of high levels of hydrocarbon pyrolysis, and eventually limits the usefulness of the fuel. A second mechanism primarily occurs at lower temperatures,

generally in the range of about 220 ° F to about 650 ° F (about 105 ° C to about 345 ° C), and involves oxidation reactions that lead to polymerization and carbonaceous gum deposits.

[0003] In the past, the solution to the problem of gum and coke formation was primarily directed toward placing limitations on fuel chemistry and impurities associated with fuels, as disclosed in U.S. Patent Nos. 2,698,512, 2,959,915 and 3,173,247. However, the propensity for gum and coke formation is increased with certain hydrocarbon fluids for fuels, oils, lubricants, petrochemical processes (plastics and synthetics) and the like, especially those derived from nonpetroleum sources, such as shale and coal, which can exhibit significantly more problems with thermal instability because of their high content of olefins, sulfur and other compounds. The consequences of thermal instability and fuel instability are of even greater significance with developing technology that requires processes and machinery to operate at higher temperatures, as afforded by advances in materials technology. Accordingly, fluid containment articles that are resistant to or prevent the formation of adverse decomposition products and foulants are necessary in applications where thermal instability, including fuel instability, is a problem as a result of exposure to such fluids to high temperatures. Particularly notable applications include the fuel-handling and hydraulic components of gas turbine engines. With the advent of higher engine operation temperatures and the use of fuel as a heat sink, there is an increased likelihood that fluid flow through such components will be restricted or even blocked by carbonaceous deposits.

[0004] It has been recognized that deposits can form as a result of a reaction between a hydrocarbon fluid and its containment wall. In U.S. Patent No. 4,078,604, heat exchangers are provided with thin-walled corrosion-resistant layers of electrodeposited gold or similar corrosion-resistant metals on the walls of the cooling channels in order to make the surfaces corrosion resistant to such storable liquid fuels as red fuming nitric acid. In this case, the wall is protected from corrosion, and the intent is not to prevent deposit formations. Furthermore, gold readily diffuses into other materials at elevated temperatures, and therefore is unsuitable as a protective coating for high temperature applications, e.g., temperatures associated with gum and coke formation.

[0005] More recently, coating systems specifically directed to inhibiting the formation and adhesion of carbonaceous deposits have been taught. For example, U.S. Patent Nos. 5,805,973, 5,891,584 and 5,923,944 and U.S. Patent Application Serial No. 09/955,043, all assigned to the assignee of the present invention and incorporated herein by reference, teach the use of coke barrier coatings (CBCs) that eliminate or modify the surface reactions which lead to formation of thermal instability deposits from hydrocarbon fluids, and reduce adhesion of such deposits. These patents are generally directed to ceramic coatings that are especially capable of reducing deposits at very high temperatures, e.g., above 650 ° F (about 345 ° C). As an example, U.S. Patent Nos. 5,805,973 and 5,891,584 disclose coatings that catalyze thermal decomposition in the hydrocarbon fluid to actually promote the formation of coke, which is substantially nonadherent to the coatings.

[0006] Many applications exist where there is a particular need for coatings that can significantly reduce the formation and adhesion of carbonaceous deposits at lower temperatures, such as fuel/air heat exchangers, fuel nozzles, oil sumps and other fuel and hydraulic system components of gas turbine engines. For this type of hardware, reductions in hydrocarbon deposits have been achieved with the use of coatings that are not reactive with hydrocarbons. In situations where heat transfer from the containment walls is a major contributor to the fluid temperature, thermally-reflective (low emissivity) coatings that reduce heat transfer to the hydrocarbon fluid have been employed to reduce deposit formation. Notably, the CBC systems taught by U.S. Patent Nos. 5,805,973, 5,891,584 and 5,923,944 and U.S. Patent Application Serial No. 09/955,043 do not have the correct optical properties, including low emissivity, to function as radiation shields. While CBC systems of the prior art can be combined with low-emissivity coatings, a significant drawback is the additional volume, weight and cost incurred. Accordingly, it would be desirable if an improved coating system were available that reduced the formation of carbonaceous deposits in hydrocarbon fluids at temperatures below about 650 ° F, reduced the adhesion of such deposits, and reduced the temperature of the hydrocarbon fluids.

Summary of Invention

[0007] The present invention provides a coating system and method for reducing the

tendency for hydrocarbon fluids, such as fuels and oils, to form carbonaceous deposits that adhere to their containment surfaces. The invention is particularly concerned with the carbonaceous deposits that form at temperatures below about 650 ° F (about 345 ° C). According to the invention, a coating system that combines an outermost layer of platinum with a ceramic barrier layer has been shown to significantly reduce the formation of carbonaceous deposits at temperatures between about 220 ° F and 650 ° F (about 105 ° C to about 345 ° C), as well as reduce the adhesion of such deposits. The platinum outermost layer also serves as a radiation shield to reduce heat transfer from the containment article to the hydrocarbon fluid. The outermost layer is preferably deposited as an extremely thin film by chemical vapor deposition. The barrier layer is deposited to a thickness sufficient to prevent interdiffusion of the platinum outermost layer with the wall on which the platinum outermost layer is deposited.

[0008] From the above, it can be seen that the coating system of this invention can be present as a very thin coating, yet performs three distinct functions that reduce hydrocarbon fluid deposits at temperatures below about 650 ° F. Accordingly, the coating system of this invention does not share the disadvantages of volume, weight and cost noted for prior attempts to combine CBCs with low-emissivity coatings.

[0009] Other objects and advantages of this invention will be better appreciated from the following detailed description.

Brief Description of Drawings

[0010] Figure 1 represents a cross-sectional view of a containment wall having a coating system in accordance with this invention.

[0011] Figures 2 and 3 are graphs that illustrate reduced deposition rates achieved with the coating system shown in Figure 1 as compared to prior art coating systems.

[0012] Figure 4 is a graph representing incident radiant energy for a fuel injector over a wavelength band of 1 to 7 micrometers.

[0013] Figure 5 is a graph showing the reflectance versus wavelength plot for the coating system of Figure 1 over that portion of the wavelength band shown in Figure 4 with

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 10

Detailed Description

[0014] Figure 1 represents a coating system 14 for a component 10 with a containment wall 12 that contacts a hydrocarbon fluid (e.g., fuels and oils) at elevated temperatures. The coating system 14 serves to prevent or at least significantly reduce the formation and adhesion of carbonaceous deposits that would otherwise adhere to the wall 12 if maintained at a temperature of up to about 650 ° F (about 345 ° C). The invention is applicable to any hydrocarbon fluid in which carbonaceous gum (or other polymers) deposits form when the fluid is subjected to elevated temperatures, generally above 140 ° C and particular at temperatures of about 220 ° F to 650 ° F (about 105 ° C to 345 ° C). Such fluids may be pure hydrocarbon or mixtures thereof. Fluid containment articles that can benefit from the present invention may be any component which is adapted to contain or transport hot hydrocarbon fluid, and include but are not limited to fuel nozzles, pipes, oil sumps and heat exchangers of gas turbine engines. With each of these examples, the containment walls of the component typically transfer heat from an external heat source to the hydrocarbon fluid within the component.

[0015] In the example represented in Figure 1, a liquid hydrocarbon fluid (not shown) contacts and flows across the surface of the wall 12 protected by the coating system 14, such that heat transferred to the fluid from an external heat source must be conducted through the coating system 14. Accordingly, the wall 12 is protected by the coating system 14 which, in accordance with this invention, reduces or prevents the formation and adhesion of carbonaceous deposits from the fuel that tend to occur as a result of the elevated temperatures of the wall 12 and fuel. The wall 12 may generally be constructed of any suitable material for the particular application. Typical materials include stainless steel, corrosion-resistant alloys of nickel and chromium, and high-strength nickel-base alloys. Notably, alloys such as these that contain iron, chromium and nickel appear to cause or promote the formation of fuel thermal decomposition products such as gum and coke in liquid hydrocarbon fluids and fuels.

[0016] The coating system 14 of this invention includes a low-emissivity platinum layer 18 and a diffusion barrier layer 16 that separates the platinum layer 18 from the wall

12 of the component 10. Though shown as consisting of only two layers, it is foreseeable that additional coating layers could be employed. The coating system 14 is preferably continuous and completely covers all surfaces of the wall 12 that would otherwise contact the fuel.

[0017] In accordance with the present invention, the platinum layer 18 of the coating system 14 is smooth, is reactive with hydrocarbon fluids at elevated temperatures and exhibits low emissivity toward the hydrocarbon fluid contained by the wall 12. The platinum layer 18 exhibits sufficiently low emissivity so that radiation heat transfer to the hydrocarbon fluid is reduced. As such, the temperature of the fluid, and therefore the tendency for the fluid to form carbonaceous deposits, is reduced. Emissivity values (ϵ) of about 0.2 or less are believed to be suitable for purposes of this invention. To promote emissivity, a preferred surface roughness for the platinum layer 18 is about 40 microinches (about 1.0 micrometer) R_a or less. This aspect of the coating system 14 also reduces the amount of time that the bulk fluid has to react near the coating surface within the fluid boundary layer, reducing both surface reaction time and concentration of deposit precursors (radicals and atoms) that provide for polymer growth.

[0018] According to this invention, hydrocarbon fluid that eventually becomes sufficiently hot to form carbonaceous gum deposits is catalyzed by the platinum layer 18 to promote the rapid formation of gum substances. It is believed that the platinum layer 18 of this invention catalyzes the formation of carbonaceous gum substances in a hydrocarbon fluid to the extent that, in a flowing fuel system, the gum substances grow too quickly to allow them to adhere to the wall 12. Instead, gum substances are found in the form of very fine particulate within the fluid.

[0019] The thickness of the platinum layer 18 should generally take into account the growth properties of platinum as it is deposited, as well as the surface roughness of the wall 12. A suitable thickness for the platinum layer 18 is about 100 to about 500 nanometers, with a more preferred range being about 150 to about 200 nanometers. In a preferred embodiment, the platinum layer 18 continuously covers the surface of the wall 12 to provide the desired chemical and reflective properties throughout the flow system where elevated wall and/or fluid temperatures are likely

[0020] The diffusion barrier layer 16 prevents interdiffusion between the platinum layer 18 and the article wall 12, which would occur at an unacceptable rate at the temperatures of concern for the invention. The barrier layer 16 also protects the wall 12 from chemical attack from contaminants in the fuel, such as sulfur and water that would form sulfuric acid and pit the surface of the wall 12. Therefore, with the protective barrier layer 16, the coating system 14 prevents or inhibits reactions between constituents of the fuel and wall 12. Preferred materials for the barrier layer 16 include ceramics such as silica (SiO_2) and alumina (Al_2O_3), though other ceramics could be used, including yttria (Y_2O_3), hafnia (HfO_2), tantalum (Ta_2O_5), mullite ($3\text{Al}_2\text{O}_3 \cdot 2\text{SiO}_2$), and complex chemical combinations of silica with boron and/or phosphorous and/or alumina. As previously noted, the thickness of the barrier layer 16 must be sufficient to prevent interdiffusion with the material of the article wall 12. While optimal thicknesses will depend in part on the composition of the barrier layer 16, a suitable thickness range is about 500 to about 1500 nanometers, with a more preferred range being about 700 to about 1300 nanometers.

[0021] According to this invention, coatings having the above-described characteristics serve to prevent or at least considerably reduce the formation, deposition and adhesion of carbonaceous gum and other decomposition impurities. As evident from the above, a requirement for the low-emissivity coating system 14 of this invention is for the barrier and platinum layers 16 and 18 to be deposited in such a manner as to obtain a suitable surface smoothness. According to the invention, a preferred deposition method is chemical vapor deposition (CVD), which is able to deposit the layers 16 and 18 on the wall 12 so that the surface finish of the coating system 14 replicates that of the underlying wall 12.

[0022] In an investigation leading to this invention, a suitable platinum layer 18 was deposited by CVD using platinum acetyl acetone ($\text{Et}_2(\text{PtOAc})_2$) as the chemical precursor, and with the following deposition parameters: deposition temperature of about 440 ° C, deposition pressure of about 500 mtorr, and a duration of about sixty minutes. The resulting platinum layer had a thickness of about 200 nanometers. Prior to depositing the platinum layer, a barrier layer 16 of silica was deposited by CVD at a temperature of about 700 ° C and pressure of about 500 mtorr, over a period of about two hours.

[0023] Figure 4 is a graph representing incident radiant energy for a fuel injector of a low-emission combustion system. Incident radiant energy is shown as peaking within a wavelength band of about 1 to 7 micrometers. In Figure 5, the reflectance versus wavelength plot for a coating system 14 in accordance with the embodiment of Figure 1 is shown over that portion of the wavelength band shown in Figure 4 with the highest incident radiant energy. Figure 5 illustrates that the CVD platinum layer 18 of this invention exhibits high reflectivity (low emissivity) over the critical wavelengths of about 2 to 6 micrometers. Accordingly, within the operating environment of the fuel injector, the platinum layer 18 of this invention is very effective in reducing radiation heat transfer from the surface on which the layer 18 is deposited to the fluid contacting the layer 18.

[0024] In another investigation leading to this invention, deposition rates were determined for tube specimens formed of Inconel 625, Inconel 718, 321 stainless steel (SS), or 347SS. Jet-A fuel was flowed through these specimens at a pressure of about 500 psi (about 345 bar) and at a flow rate of either about 10 ml/minute for about 150 hours or about 150 ml/minute for about 100 hours. The specimens were placed in a furnace where their external surfaces were heated to a temperature of about 500 ° C. The fuel was heated by the tube walls of the specimens, so that fuel temperature increased as the fuel flowed further through the length of each tube (the abscissa of Figure 2). Testing was performed with fifty uncoated specimens and fifty specimens protected by the coating system of this invention. Each coating system included a platinum layer of about 150 nanometers in thickness separated from the internal tube walls by a silica barrier layer having a thickness of about 500 to 600 nanometers. At the completion of the 150 hour test, the amount of carbonaceous deposits was measured for each specimen relative to location along the lengths of the specimens. From Figure 2, it can be seen that very little deposition occurred on those specimens protected by the coating system of this invention, while uncoated specimens experienced high deposition rates on wall portions of the specimens that sustained fuel temperatures above about 350 ° C.

[0025] A final evaluation was then performed to compare the performance of the coating system of this invention against different coating compositions. Deposition rates were again determined for twenty-five tube specimens formed of Inconel 625,

Inconel 718, 321SS or 347SS and under the same conditions as described above.

Testing was performed on ten of each of the following specimens.

[t1]

Table I

Specimen	Coating Materials
	Outer/Barrier
CBC-A	CVD tantala/CVD silica
CBC-B	CVD silica
CBC-C	CVD zirconia/CVD silica
CBC-D	CVD Pt/CVD silica

[0026] Coating thicknesses were about 150 to 200 nm for the outer layers (tantala, zirconia, platinum), and about 700 to 1300 nm for the barrier layers (silica). The total coating thicknesses of the all-silica CBC-B specimens were approximately the same as the coating thicknesses for the other specimens. As with the previous test, at the completion of about 150 hours, the amount of carbonaceous deposits was measured for each specimen relative to location along the lengths of the specimens. From Figure 3, it can be seen that very little deposition occurred on the specimens protected by the coating system of this invention (CBC-D). In contrast, those specimens coated with the other evaluated coatings experienced significantly higher deposition rates on specimen walls that sustained fuel temperatures of about 250 ° C to about 650 ° C.

[0027] While the invention has been described in terms of a preferred embodiment, it is apparent that other forms could be adopted by one skilled in the art. Therefore, the scope of the invention is to be limited only by the following claims.